



CIRCUIT-BREAKER VL 630N STANDARD BREAKING CAPACITY ICU=55KA / 415 V AC 3 POLE, LINE PROTECTION ELECTRONIC TRIP UNIT ETU12, LIG 3PHASES/3WIRES IN=630A, RATED CURRENT IR=252-630A, OVERLOAD II=1,25TO10XIN, SHORT CIRCUIT

Model		
Type of the driving mechanism / motor drive		No
Design of the overcurrent release		ETU12
General technical data		
Number of poles		3
Size of the circuit-breaker		3VL5
Electrical endurance (switching cycles) / typical		5 000
Usage category		A
Performance class for circuit breaker		N
Mechanical service life (switching cycles) / typical		10 000
Equipment marking / acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750		Q
Operating frequency / maximum	1/s	60
Voltage		
Rated operational voltage $U_e$ / max.	V	690
Insulation voltage		
• rated value	V	800
• at AC / rated value	V	800

Surge voltage resistance / rated value	kV	8
<b>Protection class</b>		
Protection class IP		IP20
Protective function of the overcurrent release		LIG
<b>Dissipation</b>		
Power loss [W]		
• maximum	W	160
<b>Electricity</b>		
Continuous current / rated value	A	630
Derating temperature / for the rated value of the continuous current	°C	50
<b>Adjustable pick-up value current</b>		
• of the current-dependent overload release / Full-scale value	A	630
• of instantaneous short-circuit trip unit / initial value	A	788
• of instantaneous short-circuit trip unit / Full-scale value	A	6 300
<b>Main circuit</b>		
<b>Operating frequency</b>		
• 1 / rated value	Hz	50
• 2 / rated value	Hz	60
<b>Operating voltage</b>		
• for main current circuit / at AC / at 50 Hz / maximum	V	690
• for main current circuit / at AC / at 60 Hz / maximum	V	690
<b>Operating current</b>		
• at 40 °C / rated value	A	630
• at 50 °C / rated value	A	630
• at 55 °C / rated value	A	598.5
• at 60 °C / rated value	A	598.5
• at 65 °C / rated value	A	504
• at 70 °C / rated value	A	504
<b>Auxiliary circuit</b>		
Number of CO contacts / for auxiliary contacts		0
Number of NC contacts / for auxiliary contacts		0
Number of NO contacts / for auxiliary contacts		0
<b>Suitability</b>		
Suitability for use		system protection

## Adjustable parameters

<b>Adjustable pick-up value current / of the current-dependent overload release / initial value</b>	A	252
---	---	-----

## Product details

<b>Product component</b>		
• Trip indicator		No
• Auxiliary switch		No
• Voltage trigger		No
• undervoltage release		No
• undervoltage release with leading contact		No
<b>Product extension / optional / motor drive</b>		Yes

## Product function

<b>Product function</b>		
• of thermal overload trip unit		adjustable
• Ground fault protection		Yes
• for neutral conductors / Short-circuit and overload proof		No
• Overload protection		Yes

## Short circuit

<b>Operational short-circuit current breaking capacity (Ics)</b>		
• at 240 V / rated value	kA	65
• at 415 V / rated value	kA	55
• at 500 V / rated value	kA	20
• at 690 V / rated value	kA	10
<b>Maximum short-circuit current breaking capacity (Icu)</b>		
• at 240 V / rated value	kA	65
• at 415 V / rated value	kA	55
• at 440 V / rated value	kA	35
• at 480 V / acc. to NEMA / rated value	kA	25
• at 500 V / rated value	kA	25
• at 600 V / acc. to NEMA / rated value	kA	20
• at 690 V / rated value	kA	20

## Connections

Arrangement of electrical connectors / for main current circuit		front side
Type of electrical connection / for main current circuit		screw-type terminals

## Mechanical Design

<b>Height</b>	mm	279.5
<b>Width</b>	mm	190
<b>Depth</b>	mm	138.5

Mounting type	fixed mounting
---------------	----------------

### Environmental conditions

<b>Ambient temperature</b>		
• during operation / minimum	°C	-25
• during operation / maximum	°C	70
• during storage / minimum	°C	-40
• during storage / maximum	°C	80

### Certificates

<b>Certificate of suitability</b>	IEC, standard switching capacity (N)
<b>Equipment marking</b>	Q
• acc. to DIN EN 61346-2	

<b>General Product Approval</b>	<b>EMC</b>	<b>Declaration of Conformity</b>
---------------------------------	------------	----------------------------------



[sonstig](#)



[TSE](#)



<b>Test Certificates</b>	<b>Shipping Approval</b>	<b>other</b>
--------------------------	--------------------------	--------------

[spezielle Prüfbescheinigung](#)  
[n](#)



[Umweltbestätigung](#)

### other

[sonstig](#)

[Bestätigungen](#)

### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3VL57631SL360AA0>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WW/view/en/3VL57631SL360AA0/all>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mfb=3VL57631SL360AA0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mfb=3VL57631SL360AA0)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://ausschreibungstexte.siemens.com/tiplv>

last modified:

11.04.2016